

WHITE TAG SPECIALS

S-B17M
Nov 2011

RECONDITIONED AND DISCONTINUED EQUIPMENT

(All equipment on this list carries a full factory Warranty, is either New Old Stock (N.O.S.) or Factory Reconditioned (F.R.) and is subject to prior sale with all sales final)

TAG NO.	QTY	MODEL NUMBER	PRICE CODE #	CONDITION	PRICE	BULLETIN
---------	-----	--------------	--------------	-----------	-------	----------

DRUM PUMP & MOTORS –Fast, safe and convenient dispensing of liquids for
Chemically aggressive liquids such as acids, alkalies , and salt solutions



ODP 450 Open Drip-proof Motor; Glass reinforced plastic housing; 0.69Hp (450 watts);
NOT SUITABLE FOR HAZARDOUS DUTY

Wt. 5.9 lbs. (2.7 kg)

WT348	3	ODP450-115	52-8008	N.O.S.	\$ 354.00	
-------	---	------------	---------	--------	-----------	--



Seal-less design, Polypropylene construction w/ Hastelloy C shaft. 16 GPM or 24' TDH. Maximum 1.4 S.G.

Wt. 7 lbs. (3.2 Kg.)

WT364	2	PP8325-3/4-ODP50	55-7012	N.O.S.	\$ 250.00	
-------	---	------------------	---------	--------	-----------	--



Mechanical seal design, Aluminum construction w/SS, Tefzel®, TFE, Carbon; For PH 3.1 – 8.3; Max temp 190° F (87° C). Includes wall bracket, bonding cable and grounding cable.

WT365	1	AL8227-1	55-7027	N.O.S.	\$ 200.00	
-------	---	----------	---------	--------	-----------	--

HORIZONTAL PUMPS - Heavy-duty metallic construction for:
Acids / Alkalies / Solvents / Wet processing solutions / D.I. Water / Fertilizers



Series 'HCI' double mechanical seal; Heavy duty cast iron w/synthetic fiber gasket & EPDM double mech. seal; 53 GPM Or 50 ' TDH @ 60 Hz; 1-1/4" NPT suction, 1" NPT discharge; 3/4Hp, 3450 RPM, 115-230V/1/60, TEFC motor

Wt. 39 lbs. (18 kg)

WT289	3	HCI1 1L(M1XM1)-C.75	61-0313 B	N.O.S.	\$ 650.00	P-108
-------	---	---------------------	-----------	--------	-----------	-------



Series 'HSS' single mechanical seal; 316 Stainless Steel w/ Teflon® gasket & Viton® single mech. seal; 160 GPM Or 90 ' TDH @ 60 Hz; 2 " NPT suction, 1-1/2 " NPT discharge; 3HP, 3450 RPM, 208-230/460v/3/60, TEFC motor

Wt. 65 lbs. (29 kg)

WT343	1	HSS1-1/2-9V(M2)-D3.0	62-0192 K	F.R.	\$ 1,250.00	P-108
-------	---	----------------------	-----------	------	-------------	-------

**PLASTIC VERTICAL PUMPS - Efficient and dependable performance for:
Acids / Caustics / cleaners / chemicals / PCB / Plating / Water / Waste water**



FPI Vertical cantilevered pump; CPVC construction w/ CPVC sleeved stainless steel shaft & EPDM O-ring, CPVC mtg. plate w/ hole for DPA, PTFE vapor seal; 400 GPM or 145 ' TDH @ 60 Hz (1514 LPM or 44.2M TDH @ 50 Hz); 180 ° F (82 ° C) max; 3" FNPT suction, 3 " MNPT discharge; 15Hp 3450 RPM, 208-230/460V/3/50-60 Hz, TEFC motor

WT324	1	P-15AK-HF	NSITEM-296	F.R.	\$ 3,450.00	
-------	---	-----------	------------	------	-------------	--



Series 'EF' Vertical cantilevered pump; CPVC construction w/ Polypro sleeved SS shaft & Viton® O-rings, PTFE vapor seal; 380 GPM or 125 ' TDH @ 60 Hz (1240 L/min or 26M TDH @ 50 Hz); 3" FNPT suction, 2 " MNPT discharge; 10Hp 3450 RPM, 208-230-460V/3/50-60 Hz, TEFC motor

WT3369	1	EF3X2-2SC-D10.0-V	45-2022 V	F.R.	\$ 3,400.00	
--------	---	-------------------	-----------	------	-------------	--



Series 'EF' Vertical cantilevered pump; CPVC construction w/ Polypro sleeved SS shaft & EPDM O-rings, PTFE vapor seal; 380 GPM or 125 ' TDH @ 60 Hz (1240 L/min or 26M TDH @ 50 Hz); 3" FNPT suction, 2 " MNPT discharge; 10Hp 3450 RPM, 208-230-460V/3/50-60 Hz, TEFC motor

WT370	1	EF3X2-2SC-D10.0-MPH	45-2022 H	F.R.	\$ 3,450.00	
-------	---	---------------------	-----------	------	-------------	--



Series 'EH' Vertical cantilevered pump; PP construction w/ PP sleeved titanium shaft & Viton ® O-rings, round. plate w/ hole for DPA, PTFE vapor seal; 100 GPM or 50 ' TDH @ 60 Hz (340 L/min or 10Mm TDH @ 50 Hz); 2" FNPT suction, 1-1/2 " MNPT discharge; 1Hp 3450 RPM, 115-230/1/50-60 Hz, TEFC motor

WT355	1	EHP1 1/2-1SC-C1.0-TV-DPA-RD	NSITEM-007	F.R.	\$ 1,500.00	
-------	---	-----------------------------	------------	------	-------------	--



Series 'EO' Vertical cantilevered pump; CPVC construction w/ CPVC sleeved Stainless Steel shaft & Viton ® O-rings, PVC mtg. plate w/ hole for DPA, PTFE vapor seal; 40 GPM or 39 ' TDH @ 60 Hz, (125 L/min or 7.4m TDH @ 50 Hz); 1-1/4" FNPT suction; 1-1/4 " MNPT DPA; 1/3Hp 3450 RPM, 115208-230V/1/50-60 Hz, TEFC motor

WT354	1	E01 CV1-C.3-MPH	39-1221 AX	N.O.S.	\$ 600.00	P-312
-------	---	-----------------	------------	--------	-----------	-------



Series 'EO' Vertical cantilevered pump; PP construction w/ PP sleeved Stainless Steel shaft & EPDM O-rings, PP round mtg. plate w/ hole for DPA, PTFE vapor seal; 40 GPM or 39 ' TDH @ 60 Hz (125 L/min or 7.4m TDH @ 50 Hz); 1-1/4" FNPT suction, 1-1/4 " MNPT DPA; 1/3Hp 3450 RPM, 208-230-460V/3/50-60 Hz, TEFC motor

WT352	1	E01 PPL1-D.3-MPH-RD	NSITEM-312	F.R.	\$ 600.00	P-312
-------	---	---------------------	------------	------	-----------	-------



Series 'EC' Vertical cantilevered pump; CPVC construction w/ CPVC sleeved Stainless Steel shaft & EPDM O-rings, PVC mtg. plate , PTFE vapor seal; 37 GPM or 47 ' TDH @ 60 Hz, (115 L/min or 10m TDH @ 50 Hz); 1" FNPT suction; 3/4 " MNPT discharge; 3/4Hp 3450 RPM, 208-230/460V/3/50-60 Hz, TEFC motor

WT371	1	ECL3/4-3SC-D.75	45-0204	F.R.	\$ 1100.00	P-304
-------	---	-----------------	---------	------	------------	-------



Series 'EC' Vertical cantilevered pump; PVDF construction w/ PVDF sleeved Stainless Steel shaft & EPDM O-rings, PTFE vapor seal; 25 GPM or 25 ' TDH @ 60 Hz, (80 L/min or 5.4m TDH @ 50 Hz); 1" FNPT suction; 3/4 " MNPT discharge; 1/3Hp 3450 RPM, 115-208-230V/1/50-60 Hz, TEFC motor

WT372	1	EKL3/4-2SC-C.3	45-0401	N.O.S.	\$1485.00	P-304
-------	---	----------------	---------	--------	-----------	-------

**SELF-PRIMING PUMPS - For transfer and re-circulation of:
Chemical solutions/Waste treatment/Agricultural Solutions/Ground water**



Series 'S'. Self-priming Pump, close coupled design, Glass reinforced polyester internal parts w/316 SS internal hardware, Viton ® "O"-rings and check valve, Carbon-Ceramic seal; 180 GPM or 85' TDH ; suction lift 25' , 2" FNPT suction, 2"FNPT discharge; 3 HP, 230/460V/3/60,3450 RPM,TEFC Motor

WT328	1	SE2HV-D3.0C	64-12H1-D3.0C	F.R.	\$ 750.00	P-613
-------	---	-------------	---------------	------	-----------	-------



Series 'I'. Self-priming Pump, pedestal mounted design, Stainless Steel housing, Glass reinforced polyester internal parts w/316 SS internal hardware & housing clamp, EPDM "O"-rings and check valve, Carbon-Ceramic seal; 170 GPM or 72' TDH ; suction lift 20' ,1-1/2/ 2" FNPT suction, 1-1/2"FNPT discharge;

WT329	1	ISE2GLL CSS	64-52G5 P	N.O.S.	\$ 675.00	P-631
-------	---	-------------	-----------	--------	-----------	-------



Series 'G'. Self-priming Pump, close coupled design, Glass reinforced Noryl ® internal parts w/316 SS internal hardware, Polypropylene basket strainer, EPDM "O"-rings , Carbon-Ceramic seal; 90 GPM or 68' TDH ; suction lift 15' , combination 2" MNPT x 1-1/2" FNPT suction & discharge; 1.5 HP, 230/460V/3/60,3450 RPM,TEFC Motor

WT346	1	GNOK1-1/2/2 DL D1.5C	60-61D4-D1.5C	F.R.	\$ 425.00	P-630
-------	---	----------------------	---------------	------	-----------	-------

AIR OPERATED DIAPHRAGM PUMPS



Air Operated Diaphragm Pump; Polypropylene construction w/Geolast® wetted materials; self-priming, run dry capabilities; 150 F (66° C) Max; 0 To 150 GPM (569 Liters/min.); 10 Ft. (3 meters) suction lift @ 100 PSI (6.8 Bars); fluid inlet/discharge 2" FNPT; 100 PSI (6.8 bars) Maximum air pressure

Wt. 54 lbs. (23.6 kg)

WT357	1	PPN- 2"	55-7208 B	N.O.S.	\$ 1950 .00	P-605
--------------	----------	----------------	------------------	---------------	--------------------	--------------



Air Operated Diaphragm Pump; Aluminum construction w/Teflon® wetted materials; self-priming, run dry capabilities; 200 F (93° C) Max; 0 To 130 GPM (492 Liters/min.); 10 Ft. (3 meters) suction lift @ 100 PSI (6.8 Bars); fluid inlet/discharge 1-1/2" FNPT; 120 PSI (8.2 bars) Maximum air pressure

Wt. 55 lbs. (24.9 kg)

WT358	1	ALTF-1-1/2"	55-7259	N.O.S.	\$ 950 .00	P-605
--------------	----------	--------------------	----------------	---------------	-------------------	--------------



Air Operated Diaphragm Pump; Stainless Steel construction w/Santoprene® wetted materials; self-priming, run dry capabilities; 200 F (93° C) Max; 0 To 40 GPM (152 Liters/min.); 15 Ft. (4.5 meters) suction lift @ 100 PSI (6.8 Bars); fluid inlet/discharge 1" FNPT; 100 PSI (6.8 bars) Maximum air pressure

Wt. 42 lbs. (19.1 kg)

WT302	1	SSL-1"	55-7255	F.R.	\$ 998 .00	
--------------	----------	---------------	----------------	-------------	-------------------	--



Air Operated Diaphragm Pump; Polypropylene construction w/Geolast® wetted materials; self-priming, run dry capabilities; 150 F (66° C) Max; 0 To 40 GPM (152 Liters/min.); 10 Ft. (3 meters) suction lift @ 100 PSI (6.8 Bars); fluid inlet/discharge 1" FNPT; 100 PSI (6.8 bars) Maximum air pressure

Wt. 19 lbs. (8.6 kg)

WT334	1	PPN-1"	55-7144 B	F.R.	\$ 615 .00	P-605
--------------	----------	---------------	------------------	-------------	-------------------	--------------



Air Operated Diaphragm Pump; Nylon construction w/Teflon® wetted materials; self-priming, run dry capabilities; 150 F (66° C) Max; 0 To 14 GPM (53.2 Liters/min.); 10 Ft. (3 meters) suction lift @ 100 PSI (6.8 Bars); fluid inlet/discharge 1/2" FNPT; 100 PSI (6.8 bars) Maximum air pressure

Wt. 10 lbs. (5.4 kg)

WT330	3	NTF-1/2"	55-7119 A	N.O.S.	\$ 475 .00	P-605
--------------	----------	-----------------	------------------	---------------	-------------------	--------------



Air Operated Diaphragm Pump; Nylon construction w/Teflon® wetted materials; self-priming, run dry capabilities; 150 F (66° C) Max; 0 To 14 GPM (53.2 Liters/min.); 10 Ft. (3 meters) suction lift @ 100 PSI (6.8 Bars); fluid inlet/discharge 1/2" FNPT; 100 PSI (6.8 bars) Maximum air pressure

Wt. 10 lbs. (5.4 kg)

WT330	3	PPTF-1/2"	55-7118 A	F.R.	\$ 475 .00	P-605
--------------	----------	------------------	------------------	-------------	-------------------	--------------



Pulsation Dampener manual adjustment; Polypropylene w/ Buna N bladder; 125 psig @ 175° F

WT342	1	DAMPENER-1/2-PP-A-L	55-7301 L	N.O.S.	\$ 500 .00	A-114
--------------	----------	----------------------------	------------------	---------------	-------------------	--------------

**MAGNETIC-COUPLED PUMPS- Reliable, trouble-free pumping for:
Waste treatment / Fume scrubbing / Chemicals / Photographic / Acids / Plating**



Series ' A ' Magnetic Coupled Pump, CPVC w/polypropylene encapsulated impeller magnet; Casing 'O' ring is EPDM and external fasteners are Stainless Steel; 1/12 HP, 2500/3000 RPM; 115-230v/1/50-60HZ, TEFC Motor; 160 F (92°C) Max., 10 GPM or 20 ' TDH @ 60 Hz (31 L/Min or 4.7m TDH @ 50 Hz); 5/8" Hose connections

Wt. 10 lbs. (4.5 kg)

WT340	2	CPP3000A	44-1372	F.R.	\$ 265.00	P-503
-------	---	----------	---------	------	-----------	-------



Series ' B ' Magnetic Coupled Pump, CPVC construction w/ECTFE impeller ; Casing 'O' ring is EPDM and external fasteners are Stainless Steel; 1/6 HP, RPM; 115v/1/60HZ, TEFC Motor; 12 GPM or 24 ' TDH @ 60 Hz ; 3/4" Hose connections

Wt. 21 lbs. (9.5 kg)

WT373	1	CPP3450BL	48-0120	F.R.	\$ 425.00	P-503
-------	---	-----------	---------	------	-----------	-------



Series ' X ' Magnetic Coupled Pump, Polypropylene construction W/Ceramic/Rulon friction surfaces ; Casing 'O' ring is Viton® and external fasteners are Stainless Steel; 1//5 HP, RPM; 115v/1/60HZ, TEFC Motor; 24 GPM or 36 ' TDH @ 60 Hz ; 1" MNPT connections

WT366	1	X200PV IT CR B C.2	81-7166 1G	F.R.	\$ 495.00	P-511
-------	---	--------------------	------------	------	-----------	-------



3/4 HP, 3450/2850 RPM, 208-230-460v/3/50-60HZ, TEFC Motor

WT356	5		44-0583 C	N.O.S.	\$ 360.00	P-504
-------	---	--	-----------	--------	-----------	-------

GRAVITY FILTRATION SYSTEMS



Polypropylene reservoir, frame, sprockets and conveyor belt. Delrin bearings, PVC shafts HDPE sludge box. Edge seals are PVC; 140 F max

WT363	2	DFS-1.5-PP	49-1415	N.O.S.	\$ 2,975.00	F-701
-------	---	------------	---------	--------	-------------	-------

FILTRATION SYSTEMS



Duplex Carbon Steel Bag Chamber System ; Carbon steel housing w/316 SS strainer basket, Viton® lid seal, differential vent ports, and adjustable support legs; 1" flange connections

WT303	1	L44241FBC15D	NSITEM-071	N.O.S.	\$ 1,750.00	
-------	---	--------------	------------	--------	-------------	--

FILTER CHAMBERS



Series 'SD' Plastic filter chamber, CPVC base and cover, PVC shell w/ CPVC internals, EPDM lid seal, Port size 1" FNPT, 3-10" DOE cartridge capacity

Wt. 13 lbs. (6 kg)

WT317	1	PL30 (1)P 1	78-1300 P	N.O.S.	\$ 185.00	C-116
--------------	----------	--------------------	------------------	---------------	------------------	--------------



Series 'K' Metal filter bag chamber; Stainless Steel housing w/ 316 SS. strainer basket, EPDM lid seal, differential drain, and vent ports, adjustable support legs 1-1/2" NPT

Wt. 90 lbs. (40.8 kg)

WT299	1	KB4SS618-1-1/2, EPDM	78-1802 S4	F.R.	\$ 950.00	C-207
--------------	----------	-----------------------------	-------------------	-------------	------------------	--------------



Series 'K' Metal filter bag chamber; Stainless Steel housing w/ 316 SS. strainer basket, VITON® lid seal, differential drain, vent ports, and adjustable support legs; 1" NPT

Wt. 40 lbs. (18 kg)

WT300	1	KB4SS412-1V, VITON	78-1801 S4V	N.O.S.	\$ 495.00	C-207
--------------	----------	---------------------------	--------------------	---------------	------------------	--------------



Series 'K' Metal filter chamber; Stainless Steel housing w/ 316 SS cup & spring assemblies, and center post, BUNA lid seal, differential drain, and vent ports, adjustable support legs; 9, 10" DOE cartridges; 1.5" NPT

Wt. 110 lbs. (49.9 kg)

WT301	2	KC4SS90 (3) S-1-1/2, EPDM	78-1855 S4	F.R.	\$1,100.00	C-207
--------------	----------	----------------------------------	-------------------	-------------	-------------------	--------------



Parker Fulflo® CH5 Filter Vessel; Carbon Steel w/zinc plate closure bolts and legs; Buna-N O-ring; 50 gpm; max 175 psi (12 bar) at 250 F; 2" NPT inlet & outlet 5, 20" DOE cartridges or 222/flat

WT362	1	CH52DT	NSITEM- 071	N.O.S.	\$ 950.00	
--------------	----------	---------------	--------------------	---------------	------------------	--



Parker Fulflo® TruBind™ 300 DOE Cartridge; 100% polyolefin construction w/Proprietary modified polymer absorbent; Polyethylene Foam gasket; 1.0 gpm per 10" cartridge; 40 psid (2.8 bar) @ 75° F (24°C) max ; 150°F (65°C) @ 20 psid (1.4 bar); 180°F (82°C) @ 10 psid (0.7 bar) Max operating temperature; 30-1/16 " (764 mm) Length; O.D. 2-1/2 " (63.5 mm); I.D. 1-1/16" (27 mm); pH Range: 2- 12

WT361	30	TBC30A-DO-A	NSITEM- 091	N.O.S.	\$ 70.00	
--------------	-----------	--------------------	--------------------	---------------	-----------------	--

KOMPRESSED-AIR-KONDITIONERS- Prevents damage to air-devices and systems



KAK Air Filter Dehydrated Clay300 SCFM @ 100 PSI; 2" NPT

WT295	5	SF-D832-2	79-0072	N.O.S.	\$ 500.00	K-101
WT367	4	VITON GASKET	550-V	N.O.S.	\$140.00	
WT368	5	EPDM GASKET	550-E	N.O.S.	\$ 15.00	

INSTRUMENTATION & CONTROLS



Conductivity Monitor; Corrosion resistant NEMA 3 enclosure; 115 vac,50-60 Hz
Comment: 0-500 micromhos conductivity measurements

WT341	1	CCM-57-500	56-0559	N.O.S.	\$.00	A-305
-------	---	------------	---------	--------	--------	-------



Conductivity Monitor; Corrosion resistant NEMA 3 enclosure; 115 vac,50-60 Hz
Comment: 0-200 PPM conductivity measurements

WT345	2	CCM-57-200	56-0558	N.O.S.	\$ 670.00	A-305
-------	---	------------	---------	--------	-----------	-------