



## SERIES 'G' | CARTRIDGE FILTER CHAMBERS

### FEATURES AND BENEFITS



- **12 Column Chamber**
- **Non-Metallic Solution Contact:**  
CPVC or Polypropylene Construction.  
(See a chemical resistance chart)
- **Heavy Duty Construction:**  
Pressure Ratings to 80psi (552 KPa)  
(See pressure/temperature table on page 2)  
Clamp Ring Closure.
- **Variety of Sizes:**  
From 12 to 60 - 10" Cartridge Capacity.  
(Or equivalent 20", 30", or 40" Lengths)
- **Port Size:**  
1-1/2" NPT Standard, BSP Optional.
- **O-Ring Seal at Cover & Vent Valve:**  
EPDM standard, FKM optional.
- **Flow Rates to 125 GPM:**  
Depending on style and length of filtration media,  
as well as chemistry characteristics.
- **Easy Service:**  
SS Swing Bolt Cover Closure with Tee Handles.  
No Tools Required.

#### Can Be Used with a Variety of Filter Media (order separately)

- Depth Wound, Pleated or Carbon Cartridges
- Positive Cartridge Seal for:  
Standard - DOE . . . Double Open End  
Optional - SOE . . . Single Open End for 222 O-Ring

### SERIES 'G' CHAMBERS: ORDER INFORMATION

MATERIAL	DESCRIPTION	MODEL NUMBER	PRICE CODE	CONN. SIZE	CARTRIDGE LENGTH
CPVC	CPVC base, cover, shell, vent valve and internals.	CL120SIO 1-1/2-G3A	78-1901-C	1-1/2" NPT	10
		CL240SIO 1-1/2-G3A	78-1902-C		20
		CL360SIO 1-1/2-G3A	78-1903-C		30
		CL480SIO 1-1/2-G3A	78-1904-C		40
		CL600SIO 1-1/2-G3A	78-1905-C		50
PP	Polypropylene base, cover, shell, vent valve and internals.	PPL120SIO 1-1/2-G3A	78-1901-PP	1-1/2" NPT	10
		PPL240SIO 1-1/2-G3A	78-1902-PP		20
		PPL360SIO 1-1/2-G3A	78-1903-PP		30
		PPL480SIO 1-1/2-G3A	78-1904-PP		40
		PPL600SIO 1-1/2-G3A	78-1905-PP		50

