





## SPACE-SAVER 'J' FILTRATION SYSTEMS Specifications (continued)

All Space-Saver 'J' systems include the following standard features:

- Non-metallic solution contact
- Stainless steel external fasteners
- Swing bolt chamber closures
- EPDM elastomers standard
- Corrosion resistant PVC hooded base
- Corrosion resistant vent valve
- Industrial duty SERFILCO pump
- Hard piping and wet testing prior to shipping
- Glycerin filled stainless steel pressure gauge
- Silicon carbide seals on mechanical seal pumps
- Filter chamber bottom inlet for low pressure drop

*Systems with polypropylene magnetic drive pump and CPVC or PVC<sup>1</sup> filter chamber*

System Number	Flow Rate		Pump Series	Pump HP <sup>3</sup>	Pump Max. PSI	Cartridge Change PSI	Filter Chamber Series	Media	Solids Area (sq. ft.)	Suction / Disch. Connections (inches)	Shipping Weight (lbs.)
	GPH @ 60 Hz	LPH @ 50 Hz									
CJ18M105	1,800	5,700	M	½	20	16	J	6 - 30"	63	1 x 1 FNPT	130
CJ24M105	1,800	5,700	M	½	20	16	J	6 - 40"	84	1 x 1 FNPT	140
CJ18M208	2,700	8,500	M	¾	24	20	J	6 - 30"	63	1½ x 1½ FNPT	135
CJ24M208	2,700	8,500	M	¾	24	20	J	6 - 40"	84	1½ x 1½ FNPT	145
CJ18M310	3,600	11,300	M	1.0	28	23	J	6 - 30"	63	1½ x 1½ FNPT	145
CJ24M310	3,600	11,300	M	1.0	28	23	J	6 - 40"	84	1½ x 1½ FNPT	155
CJ18FE215	4,700	14,800	FE	1.5	25	24	J	6 - 30"	63	2 x 1½ FNPT	155
CJ24FE215	4,700	14,800	FE	1.5	25	24	J	6 - 40"	84	2 x 1½ FNPT	165
CJ18FE320	5,000	17,300	FE	2.0	32	30	J	6 - 30"	63	2 x 1½ FNPT	170
CJ24FE320	5,000	17,300	FE	2.0	32	30	J	6 - 40"	84	2 x 1½ FNPT	180

*Systems with CPVC single or double seal<sup>2</sup> direct drive pump and CPVC or PVC<sup>1</sup> filter chamber*

System Number	Flow Rate		Pump Series	Pump HP <sup>3</sup>	Pump Max. PSI	Cartridge Change PSI	Filter Chamber Series	Media	Solids Area (sq. ft.)	Suction / Disch. Connections (inches)	Shipping Weight (lbs.)
	GPH @ 60 Hz	LPH @ 50 Hz									
CJ18HE610	3,000	9,500	HE	1.0 <sup>4</sup>	16	14	J	6 - 30"	63	2 x 1½ FNPT	155
CJ24HE610	3,000	9,500	HE	1.0 <sup>4</sup>	16	14	J	6 - 40"	84	2 x 1½ FNPT	165
CJ18HE115	4,500	14,200	HE	1.5	24	19	J	6 - 30"	63	2 x 1½ FNPT	155
CJ24HE115	4,500	14,200	HE	1.5	24	19	J	6 - 40"	84	2 x 1½ FNPT	165
CJ18HE220	5,500	17,300	HE	2.0	29	26	J	6 - 30"	63	2 x 1½ FNPT	145
CJ24HE220	5,500	17,300	HE	2.0	29	26	J	6 - 40"	84	2 x 1½ FNPT	155
CJ18HE330	6,000	18,900	HE	3.0	36	32	J	6 - 30"	63	2 x 1½ FNPT	150
CJ24HE330	6,000	18,900	HE	3.0	36	32	J	6 - 40"	84	2 x 1½ FNPT	160

<sup>1</sup> Listed system includes CPVC chamber. To order system with PVC chamber, change the **C** to **P** in System No.

<sup>2</sup> To order pump with double mechanical seal, change **HE** to **HED** in System No.

<sup>3</sup> Less than 1.0 HP — single phase standard. 1.0 HP and above — three phase standard.

<sup>4</sup> 1.0 HP 'HE' pump is 1725 RPM @ 60 Hz, 1450 RPM @ 50 Hz

**SPACE-SAVER 'J' FILTRATION SYSTEMS Optional equipment**

**OPTIONAL**

CARBON PURIFICATION CHAMBER		
DESCRIPTION		ADD TO END OF SYSTEM NO.
Includes integral carbon chamber and flow control valve. Carbon outlet 3/4" NPT	PVC chamber, Single 5" x 28" canister, 7.5 lbs. capacity	P
	CPVC chamber, Single 5" x 28" canister, 7.5 lbs. capacity	C
	CPVC chamber, Single 5" x 28" Maxi-Carb cartridge, 3.0 lbs. carbon	M

Order carbon media from Bulletin M-305.

VITON® ELASTOMERS	ADD TO END OF SYSTEM NO.
Filter chamber and pump	V

MOTOR STARTERS	
NEMA 4X Watertight push button (mounted and wired)	PRICE CODE NO.
Add -S to motor starter Price Code No. when ordering motor starter for use with DRI-STOP® Pump Protector	115 - 230V/1/50-60
<b>IMPORTANT:</b> Specify operating voltage	230 - 460V/3/50-60
	O-MS1P
	O-MS3P

DRI-STOP® PUMP PROTECTOR	
DRI-STOP 2R for use with double mechanical seal pump.	O-2DS2R
DRI-STOP 3 for use with magnetic drive or single mechanical seal pump.	O-DS3C

OPERATING VOLTAGE	
1 horsepower and above - Single phase	O-1PH
Under 1 horsepower - Three phase	O-3PH

50 Hz OPERATION	
Single phase @ 50 Hz	O-150H
Three phase @ 50 Hz	O-350H

F.O.B. Northbrook, Illinois

Specifications subject to change without notice.

Registered trademark: Viton - DuPont Dow Elastomers



**SERFILCO®**

2900 MacArthur Blvd. 847-509-2900  
Northbrook, IL 60062-2005 U.S.A. 800-323-5431  
e-mail: sales@serfilco.com FAX: 847-559-1141  
www.serfilco.com

DISTRIBUTED BY