

Customize your Guardian with the following options

SLURRY TANK and VALVES			
	SURFACE AREA (sq. ft.)	SLURRY CAPACITY (gal.)	PRICE CODE NO.
SV4 For chemical mixing, pump priming or precoating. Includes polyethylene tank w/CPVC frame, CPVC piping and four CPVC ball valves and tank strainer.	84	7	O-2084
	126	11	O-2072
	168 +	18	O-2090
SV6 Same as above, plus backwash and bypass valves.	84	7	O-2085
	126	11	O-2073
	168 +	18	O-2091

MOTOR STARTERS		
NEMA 4X Watertight push button (mounted and wired)		PRICE CODE NO.
Add -S to motor starter Price Code No. when ordering motor starter for use with DRI-STOP® Pump Protector IMPORTANT: Specify operating voltage	115 - 230V/1/50-60 230 - 460V/3/50-60	O-MS1P O-MS3P
DRI-STOP® PUMP PROTECTOR		
DRI-STOP 2R for use with double mechanical seal pump.		O-2DS2R
DRI-STOP 3 for use with magnetic drive or single mechanical seal pump.		O-DS3C

CARBON PURIFICATION CHAMBER		
Includes extended base, adapter kit, flow control valve and drain valve.		
DESCRIPTION	CARBON CAPACITY	PRICE CODE NO.
PVC chamber and internal canister(s) for use with granular carbon. For CPVC chamber, add C to end of Price Code No.	Single 5" x 28" canister, 7.5 lbs. capacity Triple 5" x 28" canister, 22.5 lbs. capacity Triple 5" x 48" canister, 42 lbs capacity	O-1528 O-3528 O-3548

Order carbon media from Bulletin M-305.

PORTABLE	PRICE CODE NUMBER
Two fixed wheels, two swivel casters, pull handle	O-2042
OPERATING VOLTAGE 50 Hz	
Single phase @ 50 Hz Three phase @ 50 Hz Specify operating voltage	O-150H O-350H
VITON® ELASTOMERS	ADD TO END OF SYSTEM NO.
Filter chamber and pump	V